

# MODEL 2125

## EXCESS FLOW VALVE



The Model 2125 Excess Flow Valve is designed for use in liquid, gas or vapor service. The 2125 comes standard with 150#, 300#, or 600# ANSI/ASME class flanges. The 2125 is a high flow version of the model 2120 to allow for substantially lower pressure drops. Options for this model include No Reset (standard), automatic reset, manual bypass, and other options can be added. These valves are heavily constructed to withstand years of service. This model allows for an increase in flow rates over the normal valves without increasing line size.

FLANGE SIZE	150#			300#			600#		
	A	B	C	A	B	C	A	B	C
1"	5.00"	4.25"	0.50"	8.00"	4.88"	0.62"	8.50"	4.88"	0.69"
1.5	6.50	5.00	0.62	9.00	6.12	0.75	9.50	6.12	0.88
2	8.00	6.00	0.69	10.50	6.50	0.81	11.50	6.50	1.00
3	9.50	7.50	0.88	12.50	8.25	1.06	14.00	8.25	1.25
4	11.50	9.00	0.88	14.00	10.00	1.19	17.00	10.75	1.50
6	16.00	11.00	0.94	17.50	12.50	1.38	22.00	14.00	1.88
8	19.50	13.50	1.06	22.00	15.00	1.56	26.00	16.50	2.19
10	24.50	16.00	1.12	24.50	17.50	1.81	31.00	20.00	2.50
12	27.50	19.00	1.19	28.00	20.50	1.94	33.00	22.00	2.62
14	31.00	21.00	1.31	33.00	23.00	2.06	35.00	23.75	2.75

These dimensions are for standard designs as reference only.  
Valves can be custom-engineered as needed.

Typical dimensions are listed. Data contained herein can be altered to accommodate design changes and changes to increase performance. Information on this page is the sole property of L6 Inc. d/b/a Total Valve Systems

